Source Apportionment of Total Suspended Particulate Matter in Coarse and Fine Size Ranges Over Delhi

Arun Srivastava*, Sandeep Gupta, V. K. Jain

School of Environmental Sciences, Jawaharlal Nehru University, New Delhi – 110 067, India

Abstract

Source apportionment of total suspended particulate matter (TSPM) and associated heavy metals has been carried out for the city of Delhi using the Chemical Mass Balance Model, Version 8 (CMB8), as well as principle component analysis (PCA) of SPSS (Varimax Rotated Factor Matrix method) in coarse- and fine-size mode. Urban particles were collected using a five-stage impactor at six sites in the winter of 2005-06. The impactor segregates the TSPM into five different size ranges (viz. > 10.9, 10.9-5.4, 5.4–1.6, 1.6–0.7 and $< 0.7 \mu m$). Four samples were collected from six different sites every 24 hours. Samples were analyzed in five size ranges gravimetrically and chemically for the estimation of SPM and metals. The five different size ranges were divided into two broad categories: coarse (1.6 to >10.9 μ m) and fine (< 1.6 μ m). The CMB8 and PCA were executed separately for both coarse and fine size ranges. Results obtained by CMB8 indicate the dominance of vehicular pollutants (62%), followed by crustal dust (35%) in the fine size range; while in the coarse size range crustal dust dominated (64%) over vehicular pollution (29%). Little contribution from paved-road dust and industrial sources was observed. Results of PCA (or factor analysis) reveal two major sources (vehicular and crustal resuspension) in both coarse and fine size ranges. The correlations of factors (sources) with the metals show that in the coarse size range the dominant source is crustal re-suspension (68%) followed by vehicular pollution (23%). However, this is reversed in the case of the fine size range factor analysis where vehicular pollution (86%) dominated over crustal re-suspension (10%).

Keywords: Source apportionment; Chemical mass balance; Principle component analysis; Coarse particles; Fine particles; Delhi.

INTRODUCTION

+91 11 2671 7502

E-*mail address:* a_srivastava@mail.jnu.ac.in, srivastava02@hotmail.com

Delhi, the capital of India is one of the 10 most polluted cities in world. It is the second largest Indian city with a population of over 14 million, with 1.3% of India's population. The

^{*}Corresponding author. Tel.: +91 11 2670 4322; Fax:

annual average growth rate of Delhi's population is 3.85%, but the annual average vehicular growth rate is 5.85% (Economic Survey of Delhi, 2006). The transportation network in Delhi is predominantly road based with 1284 km of road per 100 km². Over 4.8 million vehicles travel Delhi's roads today. The number of vehicles is expected to reach 26 million in 2011. It is estimated that over 3000 metric tons of air pollutants are emitted in Delhi daily (MOEF, 2002).

This alarming vehicular growth rate, frequent traffic jams and not much improvement in the number of roads has resulted in a significant rise in the TSPM (total suspended particulate matter) level of Delhi. However, although vehicles continue to be the biggest contributor to the Delhi's ambient TSPM level, significant contributions from other pollution sources, such as roadside dust, industries, trans-boundary migrations, power plants, solid waste and local sources, have also been observed (Srivastava and Jain, 2006; Srivastava and Jain, 2007). Particulate matter from these sources may contain hazardous pollutants and can have carcinogenic and mutagenic effects. Thus, identification of the sources and estimates of their contributions are important.

Several methods are used to estimate source contributions, including principle component analysis (PCA or Factor Analysis), multiple linear regression analysis (MLR) and the Chemical Mass Balance (CMB) Receptor Model. In the present investigation, we have applied both CMB and PCA for the source apportionment of TSPM in the ambient air of Delhi. CMB models are fundamental receptor models and very useful for coarse and fine particle source apportionment (CMB8, 1997). CMB models estimate source contributions by determining the best-fit combination of emission source chemical composition profiles needed to reconstruct the chemical composition of ambient samples (Watson *et al.*, 1991; Watson *et al.*, 1994; Schauer *et al.*, 1996). While the PCA method focuses on cleaning up the factors, it also produces factors that have high correlations with one smaller set of variables and little or no correlation with another set of variables (Stevens, 1996).

Many studies have been conducted on the source apportionment of different fractions of TSPM and metals in various parts of the world using different techniques (Artaxo et al., 1990; Kashara et al., 1990; Watson et al., 1994; Anderson et al., 1995; Hidy et al., 1996; Vega et al., 1997; Adgate et al., 1998; Liu et al., 1998; Biegalski et al., 1998; Batterman et al., 1988; Cheng et al., 1989; Ames et al., 2000; Bhave et al., 2001; Billheimer, 2001; Chen et al., 2001; Chow et al., 2002; Christensen et al., 2004; Salma et al., 2005; Arditsoglou and Samara 2005; Gupta et al., 2006). Recently, some important studies have been carried out using CMB receptor models and the PCA method: Breed et al. (2002) determined the possible sources of PM_{10} in Prince George (Canada) based on morphology and in situ chemical composition of the particulate matter. Samara et al. (2003)applied CMB source apportionment of PM₁₀ in an industrialized urban area of northern Greece. Samara (2005) identified sources of TSP using CMB in a lignite burning area of Macedonia, Greece.

Zheng (2005) studied the seasonal trend of sources of $PM_{2.5}$ in Beijing.

However, in India studies on source apportionment by CMB are rather limited. Sharma and Patil (1992, 1994) used CMB and PCA respectively for source apportionment of aerosols in Bombay. Srivastava (2004) and Srivastava et al. (2005) carried out source apportionment of ambient VOCs in Mumbai and Delhi, respectively, using CMB8. Srivastava and Jain (2007a,c) carried out source apportionment studies using CMB and PCA, respectively, on data collected in 2001. In the present study, we assessed the air quality of Delhi at a time when almost all the public transport is compressed natural gas (CNG) fueled and metro rails have been introduced on some fixed routes. In this paper, an attempt has been made to assess the various sources of fine and coarse particulates in Delhi using CMB8 and PCA methods.

MATERIALS AND METHODS

Area descriptions



Fig. 1. Wind rose pattern of Delhi during sampling (Dec 10, 05 – Jan 20, 06).

Sampling was carried out at six different sites in Delhi. Delhi has three coal-based thermal power plants and over 125,000 industrial units (Government of India, 2001). It lies in the subtropical belt, characterized by a semi-arid climate, which consists of summer (March-May), monsoon (June-Aug), post-monsoon (Sep-Nov) and winter (Dec-Feb) seasons. It experiences a maximum temperature of ~45-48°C in June during summer and a minimum of ~1–2°C in January during winter. It has a normal annual rainfall of 611 mm. The air over Delhi is dry most of the year. Humidity is high in the monsoon season, while April and May are the driest months. Winds are predominantly westerly or northwesterly and tend to be more northerly in the afternoons, except in the monsoon season, when it is easterly and northeasterly. Yearly mean wind speed varies in the range of 0.9-2.0 m/s. The April to June period witnesses the highest frequency of thunderstorms and dust storms. These storms are generally dry, but some are accompanied by heavy rains. During the course of sampling, max, min temperature and max, min relative humidity were 21.0, 4.9°C and 90.4, 45.0%, respectively. The wind rose pattern of Delhi is shown in Fig. 1.

Sampling sites

Sampling was performed from December 10, 2005 to January 20, 2006 at six different sites. Their locations are indicated in Fig. 2. The details of each category of sites and number of samples along with the sampling duration are given in Table 1.

Table 1. Sampling details.				
Site	Site character	Sampling period	Number of samples	
Jawaharlal Nehru University	Sensitive site	24 h	Four	
Uttam Nagar	Residential site	24 h	Four	
Nizamuddin	Sensitive site	24 h	Four	
ΙΤΟ	Heavy traffic site	24 h	Four	
Okhla	Industrial site	24 h	Four	
Cannaught Place Commercial site		24 h	Four	



Fig. 2. Locations of sampling sites (not to scale).

Sampling procedure

Sampling was done with a five-stage cascade

particulate separator (Kimoto Electric Co. Ltd. Japan). It was operated at an average flow rate

		1	1	
Stage	Size range of particles	Shape of filter	Measurement of filter (mm)	
1	> 10.9 µm	Doughnut	197.5 (outer diameter), 171.6 (inner diameter)	
2	10.9–5.4 μm	Doughnut	177.5 (outer diameter), 147.5 (inner diameter)	
3	5.4–1.6 µm	Doughnut	149.5 (outer diameter), 120.6 (inner diameter)	
4	1.6–0.7 μm	Doughnut	132.0 (outer diameter), 97.6 (inner diameter)	
5	< 0.7	Rectangular	203×254	

Table 2. Description of the different sizes of particles and filters.

of 600 L/min with 24 h continuous samples obtained from each site for four days. The samples were collected on EPM-2000, Whatman GF/A glass fiber filters. Each set of samples consisted of five different sized filters for various size ranges. The size ranges of the particles and the sizes of corresponding filters used for each size are provided in Table 2. The filters were kept in vacuum desiccators for 24 h to remove any moisture content, and then weighed by a precision micro balance (Mettler AE 50). Afterwards, they were mounted on the air sampler. After sampling, the filters were immediately transferred to vacuum desiccators to again de-moisturize in the same manner and then again weighed. The difference in pre- and post-sampling weights were used for the estimation of TSPM.

Analysis

Acid digestion, required for the metals determination by AAS, was carried out according to a standard procedure (Katz, 1977). Acid digestion was performed in Teflon bombs following these steps. Step 1: Sub samples of dry filters were dissolved in 3 mL HF, 6 mL HNO₃ and 1.5 mL HCl in Teflon bombs at 120°C for 1 h; Step 2: Digestates were evaporated to dryness at 70°C for 1/2 h; Step 3: Residues were re-dissolved in 10 mL of 10 M HNO₃ and evaporated to dryness. Step 3 was repeated until residues were fully dissolved. A series of blanks were prepared using the same digestion method. Standard solutions of metals were prepared as described in the USEPA manual (1983) and AAS manual (1983). Metals and reagents used for standard solutions were of AR grade. The reagents used were HNO₃ 70% (S.G. 1.41), HCl 36% (S.G. 1.18) and HF 40% (S.G. 1.13).

Source apportionment methodology

To carry out source apportionment in two different size ranges the samples collected were broadly divided in two categories: coarse and fine. Coarse size particles represented the sum total of particles of size ranges: > 10.9, 10.9–5.4 and 5.4–1.6 μ m, while the fine particles represented the sum total of particles of size ranges: 1.6–0.7 and < 0.7 μ m. To gain a better understanding of the dominant sources in Delhi, two different source apportionment techniques were applied: Chemical Mass Balance Receptor Model, Version 8 (CMB8) and the Principle Component Analysis (PCA).

Chemical mass balance model

Table 3. Some of the CMB performancestatistics.

Size	R^2	R/U	χ^2
Coarse	0.98	0.99	3.84
Fine	0.96	3.80	1.49

In this study, a chemical mass balance receptor model, CMB8 (CMB, 1997; USEPA, 1997; Watson *et al.*, 1997) was used to apportion the sources contributing to the ambient coarse and fine particles in Delhi. The basic principle of the receptor model may be expressed by an empirical relationship given in Eq. (1). This represents the relationship between the concentrations of the chemical species measured at the receptor site to those emitted from the source.

$$C_i = \sum_{J=1}^{P} F_{ij} \times S_j \tag{1}$$

Where C_i is the ambient concentrations of the species *i*, measured at the receptor site, *P* is the number of sources that contribute, F_{ij} is the fraction of the emissions of the species *i* starting from the source *j*, and S_j the ambient contribution of the source *j*. The model fit is considered 'good' if the values of the following statistical parameters lie within the acceptable range given along with them (Watson *et al.*, 1997):

(i) Fraction of variance in measured concentrations, explained by the variation in

calculated concentrations (\mathbb{R}^2) more than 0.8, Weighted sum of squares of the difference between calculated and measured fitting species concentration (χ^2) less than 4,

(ii)Degree of freedom (DF) greater than 5,

(iii) Percent of aerosol mass explained by sources between 80-120,

(iv) Ratio of calculated to measured concentration (C/M ratio) between 0.5 - 2, and

(v)Absolute value of ratio of residual to uncertainty (R/U) less than 4.

Source profiles

The sources of 11 metals (Mn, Cr, Cd, Cu, Co, Pb, Ni, Fe, Zn, Mg and Ca) for both coarse and fine suspended particles were determined. It is important to note that the source profiles for Indian cities have not been compiled. Thus, the metals source profiles used were taken from the USEPA (Speciate 3.2, 2002) database and some of the previous work carried out in Delhi (Khemani et al., 1985; Mehra et al., 1998; Balachandran et al., 2000; Gadi et al., 2000; Anju and Banerjee, 2003; Srivastava and Jain 2003; Khillare et al., 2004; Monkkonen et al., 2004; Srivastava and Jain 2005; Yadav and Rajamani 2006; Srivastava and Jain 2007a,,b,c). The emission sources considered were (i) Soil and crustal dust, (ii) Paved road dusts, (ii) Vehicular emissions, and (iv) Industrial sources.

Principle component analysis

To identify and estimate the possible sources of coarse and fine size particles, a PCA, or factor analysis, method was applied. PCA was performed by the Varimax Rotated Factor Matrix method, based on the orthogonal rotation criterion which maximizes the variance of the squared elements in the column of a factor matrix, using a statistical package SPSS (Version 9). This method focuses on cleaning up the factors. It produces factors that have high correlations with one smaller set of variables and little or no correlation with another set of variables (Stevens, 1996).

RESULTS AND DISCUSSION

Source apportionment was carried out for both coarse and fine size ranges of TSPM using CMB8 and PCA methods. The results of their analyses are discussed below.

Source apportionment using cmb8 receptor model



Fig. 3. Mean mass size distribution of daily (24 h) average TSPM

Source contributions from various sources in the coarse and fine size ranges are provided in Fig. 3. Table 2 gives the R² values along with the range of ratio R/U and χ^2 values. In the fine size range, vehicular emissions are the dominant source. In the case of the coarse fraction, crustal dust is most dominant. The industrial contribution is more or less the same



Fig. 4. Daily (24 h) average concentration of different of metals.



Fig. 5. Source contribution to TSPM in coarse and fine particle range by CMB 8.

in both coarse and fine size fractions; i.e., 3 and 2%, respectively. The contribution from paved road dust is somewhat more for coarse particles (4%) than fine particles (1%). The results obtained in this study are not in agreement with those from the previous study by Srivastava and Jain (2007a) in which it was observed that vehicular pollution dominates in both coarse and fine size ranges. This study was carried out before the implementation of compressed natural gas vehicles (CNG). Therefore, we can conclude that after the implementation of CNG, although vehicles continue to be the largest polluters of Delhi's ambient air, their over-contribution is now confined to fine particles only, while soil and crustal dust are now the predominant contributors to coarse particles.

Source apportionment by PCA

To validate the results obtained by CMB, a PCA was performed by the Varimax Rotated Factor Matrix method of SPSS for both coarse and fine size fractions. Sites were assumed to be repetitive of data, while metals were treated as the variable. A total of nine components were obtained, out of which two were extracted as principle components (Eigenvalue > 1) for both coarse and fine size ranges. The detailed results are given in Table 4. In case of coarse particles, two PCs were obtained, first and second PCs contribute about 68 and 23%, respectively. Considering a correlation coefficient of ≥ 0.5 , the metals correlated with factor 1 points it to be the crustal re-suspension source and factor 2 as the vehicular source. It is important to note that the metals generated from various sources

Table 4. Varimax rotated factor loading matrix.			
Size Range	Variable	Factor 1	Factor 2
Fine	Cu	0.405	
Particles	Pb		
	Fe		
	Cd		
	Cr	0.499	
	Zn	0.355	
	Ni	0.328	0.428
	Mg		0.992
	Co		
	Mn		
	Ca	0.487	0.874
Eigenvalues		96.853	11.286
% of		85.609	9.975
Variance			
Cumulative		85.609	95.585
%			
Possible		Vehicular	Crustal re-
Source			suspension
Coarse	Cu		0.990
Particles	Pb		
	Fe	0.426	
	Cd	0.669	
	Cr	0.551	
	Zn	0.780	
	Ni	0.356	0.675
	Mg	0.644	
	Co		0.675
	Mn	0.395	
	Ca	0.961	
Eigenvalues		21.674	7.242
% of		67.936	22.700
Variance			
Cumulative		67.936	90.636
%			
Possible		Crustal re-	Vehicular
Source	<u>.</u>	suspension	-

also become part of crustal dust over time (Khemani *et al.*, 1985; Balachandran *et al.*, 2000; Anju and Banerjee, 2003; Monkkonen *et al.*, 2004; Khillare *et al.*, 2004). The condition is reversed in the case of fine particulate source apportionment. Again, two PCs were obtained, contributing about 86 and

Size range	Model used –	Source contribution (%)			
		Vehicles	Crustal dust	Industries	Paved-road dust
Fine	CMB8	62 %	35 %	2 %	1 %
	PCA	86 %	10 %	Not clear	Not clear
Coarse	CMB8	29 %	64 %	3 %	4 %
	PCA	23 %	68 %	Not clear	Not clear

Table 5. Source contributions by both CMB 8 and PCA models.

10% respectively. The correlation between metals and factors suggests factor 1 as vehicular source and factor 2 as crustal redifferentiation suspension. The between vehicular source and crustal re-suspension was made keeping in mind the association of Ca and Mg, because these metals are not associated with vehicular pollution. It was also confirmed from the enrichment factor discussed previously that Ca and Mg at various sites are mainly of crustal origin.

CONCLUSIONS

Source apportionment carried out by both CMB8 and PCA identified two major sources: vehicular and crustal dust (crustal re-suspension for PCA). Results of the CMB8 and uses also revealed the contributions of paved road dust and industrial pollutants to be small in both the coarse and fine size ranges. It has also been observed that the over-dominance of vehicular pollutants are now (2005-06) confined to fine particles only, while they dominated both coarse and fine particles during pre-CNG implementation era (2001).

ACKNOWLEDGEMENTS

This study was sponsored and funded by the

Department of Science and Technology (DST), Government of India, New Delhi in the form of the Young Scientist Project (SR/FTP/ES-19/2004) to Arun Srivastava. Authors acknowledge Dr. S. K. Tyagi (CPCB, New Delhi), Dr. Rajendra Prasad (Envirotech Instruments Pvt. Ltd., New Delhi) and other persons for their permission to carry out sampling at their offices or residences. Special thanks to J.G. Watson, J.C. Chow and N.F. Robinson at Desert Research Institute (DRI) and Anjali Srivastava for their assistant with the CMB8 model.

REFERENCES

- AAS Manual, (1983). Phillips Analytical AAS Data Book. Bear Press Limited, Cambridge, England.
- Adgate, J.L., Willis, R.D., Buckley, T.J. Chow,
 J.C., Watson, J.G., Rhoads, G.G. and Lioy,
 P.J. (1998). Chemical Mass Balance Source
 Apportionment of Lead in House Dust. *Environ. Sci. Technol.* 32: 108-114.
- Ames, M.R. Gullu, G., Beal, J. and Olmez, I. (2000). Receptor Modeling for Elemental Source Contributions to Fine Aerosols in New York. *JAWMA*. 50: 881-887.
- Anderson, M.K. and Brookman, E.T., Preliminary Analyses at a PM₁₀ Sampling

Site Using a Combined Source Apportionment Approach. Prepared by TRC Environmental Consultants, East Hartford, CT, 1995.

- Anju and Banerjee, D.K. (2003). Heavy Metal Levels and Solid Phase Speciation in Street Dusts of Delhi, India. *Environ. Pollut.* 123: 95–105.
- Arditsoglou, A. and Samara, C. (2005). Levels of Total Suspended Particulate Matter and Major Trace Elements in Kosovo: A Source Identification and Apportionment Study. *Chemosphere*. 59: 669-678.
- Artaxo, P., Andrade, F. and Maenhaut, W. (1990). Trace Elements and Receptor Modeling of Aerosols in the Antarctic Peninsula. *Nuclear Inst Methods. Phy. Res.* B49: 383-387.
- Balachandran, S., Meena, B.R. and Khillare, P.S., (2000). Particle Size Distribution and its Elemental Composition in the Ambient Air of Delhi. *Environ. Int.* 26: 49–54.
- Batterman, S.A., Dzubay, T.G. amdBaumgardner R.E. (1988). Development ofCrustal Profiles for Receptor Modeling.*Atmos. Environ.* 22: 1821-1828.
- Bhave, P.V., Fergenson, D.P., Prather, K.A. and Cass, G.R. (2001), Source Apportionment of Fine Particulate Matter by Clustering Single-particle Data: Tests of Receptor ModelAccuracy. *Environ. Sci. Technol.* 35: 2060-2072.
- Biegalski, S.R., Landsberger, S. and Hoff,R.M. (1998), Source-receptor ModelingUsing Trace Metals in Aerosols Collected atThree Rural Canadian Great LakesSampling Stations. JAWMA. 48: 227-237.

- Billheimer, D. (2001). Compositional Receptor Modeling. *Environmetrics*. 2: 451-467.
- Breed, C.A., Arocena, J.M. and Sutherland, D. (2002). Possible Sources of PM_{10} in Prince George (Canada) as Revealed by Morphology and in Situ Chemical Composition of Particulate. *Atmos. Environ.* 36: 1721–1731.
- Chemical Mass Balance Receptor Model Version 8 (CMB8), User Manual, US EPA Research Triangle Park, NC, Desert Research Institute, Reno, N.V., 1997.
- Chen, K.S., Lin, C.F. and Chou, Y.M. (2001). Determination of Source Contributions to Ambient PM_{2.5} in Kaohsiung, Taiwan, using receptor model. *JAWMA*. 51: 489-498.
- Cheng, M.D. and Hopke, P.K. (1989). Identification of Markers for Chemical Mass Balance Receptor Model. *Atmos. Environ.* 23: 1373-1384.
- Chow, J.C. and Watson, J.G. (2002), Review of PM2.5 and PM10 apportionment for fossil fuel combustion and other sources by the chemical mass balance receptor model. *Energy Fuels.* 16: 222–260.
- Christensen, W.F. (2004). Chemical Mass Balance Analysis of Air Quality Data when Unknown Pollution Sources are Present. *Atmos. Environ.* 38: 4305-4317.
- Economic Survey of Delhi, 2005-06. *Published by the Planning Department, Government of NCT of Delhi, Delhi Secretariat, New Delhi.*
- EPA Manual, (1983). Methods of ChemicalAnalysis of Water and Wastes.USEnvironmentalProtectionAgency,

Cincinnati, OH.

- Gadi, R., Singh, N., Sarkar, A.K. and Parashar,
 D.C. (2000). *Mass Size Distribution and Chemical Composition of Aerosols at New Delhi*. In Pollution in Urban Environment,
 K. Siddappa, S. Sadasivan, V.N. Sastri, K.P.
 Eappen, R.K. Somashekar, and N.
 Manamohan Rao, Eds. Bangalore
 University, Bangalore, p. 30-32
- Government of India, White Paper on Pollution in Delhi with an Action Plan, Ministry of Environment and Forests, Paryavaran Bhawan, New Delhi, 2001.
- Gupta, A.K., Karar, K., Srivastava, A., (2006).
 Chemical Mass Balance Source
 Apportionment of PM₁₀ and TSP in
 Residential and Industrial Sites of an Urban
 Region of Kolkata India. *J. Hazard. Mater.*142: 279–287.
- Hidy, G.M. and Venkataraman, C. (1996). The Chemical Mass Balance Method for Estimating Atmospheric Particle Sources in Southern California. *Chem. Eng. Commun.* 151: 187-209.
- Kasahara, M., Choi, K.C. and Takahashi, K. (1990). Source Contribution of Atmospheric Aerosols in Japan by Chemical Mass Balance Method. *Atmos. Environ.* 24A: 457-466.
- Katz, M., (1977). *Methods of Air Sampling* and Analysis. 2nd Ed. APHA.
- Khemani, L.T., Naik, M.S., Momin, G.A.,
 Kumar, R., Chatterjee, R.N., Singh, and
 Ramana Murty, B.V. (1985). Trace
 Elements in the a Tmospheric Aerosols at
 Delhi, North India. J. Atmos. Chem. 273–285.

- Khillare, P.S., Balachandran, S. and Meena,B.R., (2004). Spatial and TemporalVariation of Heavy Metals in AtmosphericAerosol of Delhi. *Environ. Monit. Assess.*90: 1–21.
- Liu, X., Feng, Y., Jia, H., Zhang, Y., Ma, Q. and Shao, Y. (1998). Source Apportionment of Qingdao Atmospheric Aerosol with Ahemical Mass Balance Method. *Res. Environ. Sci.* 11: 51-54.
- Mehra, A., Farago, M. E. and Banerjee, D. K., (1998). Impact of Fly Ash from Coal-Fired Power Stations in Delhi, with Particular Reference to Metal Contamination. *Environ Monit Assess.* 50: 15 35.
- MoEF. (2002). Agenda 21: An Assessment. Prepared by Tata Energy Research Institute on Behalf of Ministry of Environment and Forests, Government of India, New Delhi.
- Monkkonen, P., Uma, R. Srinivasan, D., Koponen, I.K., Lehtinen, K.E.J., Hameri, K., Suresh, R., Sharma, V.P. and Kulmala, M. (2004). Relationship and Variations of Aerosol Number and PM₁₀ Mass Concentrations in a Highly Polluted Urban Environment - New Delhi, India. *Atmos. Environ.* 38: 425–433.
- Salma, I., Ocskay, R., Raes, N. and Maenhaut,W. (2005). Fine Structure of Mass SizeDistributions in an Urban Environment.*Atmos Environ.* 39: 5363-5374.
- Samara, C. (2005). Chemical Mass Balance Source Apportionment of TSP in a Lignite Burning Area of Western Macedonia, Greece. *Atmos. Environ.* 39: 6430–6443.
- Samara, C., Kouimtzis, T., Tsitouridou, R., Kanias, G. and Simeonov, V. (2003).

Chemical Mass Balance Source Apportionment of PM_{10} in an Industrialized Urban Area of Northern Greece. *Atmos. Environ.* 37: 41–54.

- Schauer, J.J., Rogge, W.F., Hildemann, L.M., Mazurek, M.A. and Cass, G.R. (1996).
 Source Apportionment of Airborne Particulate Matter Using Organic Compounds as Tracers. *Atmos. Environ.* 30: 3837–3855.
- Sharma, V.K. and Patil, R.S. (1992). Size Distribution of Atmospheric Aerosols and Their Source Identification Using Factor Analysis in Bombay, India. *Atmos. Environ.* 26, 135-141.
- Sharma, V.K. and Patil, R.S. (1994). Chemical mass balance model for source apportionment of aerosols in Bombay. *Environ. Monit. Assess.* 29: 75-88.
- Speciate 3.2, USEPA (2002). Particulate Matter (PM) speciation data system. USEPA, QAQPS Research Triangle Park, North Carolina.
- Srivastava, A. (2004). Source Apportionment of Ambient VOCs in Mumbai City. *Atmos. Environ.* 38: 6829–6843.
- Srivastava, A. and Jain, V.K. (2005). A Study to Characterize the Influence of Outdoor TSPM and Associated Metals on the Indoor Environments in Delhi. *J. Environ Sci Eng.* 47: 222-231.
- Srivastava, A. and Jain, V.K. (2003).Relationships between Indoor and Outdoor Air Quality in Delhi. *Indoor Built Environ*. 12: 159-165.
- Srivastava, A. and Jain, V.K. (2007a). Seasonal Trends in Coarse and Fine Particle

Sources in Delhi by the Chemical Mass Balance Receptor Model. *J. Hazard. Mater.* 144: 283–291.

- Srivastava, A. and Jain, V.K. (2007b). A Study to Characterize the Suspended Particulate Matters in an Indoor Environment in Delhi, India. *Build Environ*. 42: 2046–2052.
- Srivastava, A. and Jain, V.K. (2007c). Size
 Distribution and Source Identification of
 Suspended Particulate Matters in
 Atmospheric Aerosols Over Delhi. *Chemosphere.* 68: 579-589.
- Srivastava, A. Sengupta, B. and Dutta, S.A. (2005). Source Apportionment of Ambient VOCs in Delhi City. *Sci. Total. Environ.* 343: 207–220.
- Stevens, J. (1996). Applied Multivariate Statistics for the Behavioral Sciences (3rd ed.). Mahwah, Erlbaum, NJ.
- USEPA, (1997). *Compendium Method TO-14A*, EPA/625/R-96/ 010b.
- Vega, E. García, I. Apam, D., Ruíz, M.E. and Barbiaux M. (1997). Application of a Chemical Mass Balance Receptor Model to Respirable Particulate Matter in Mexico City. JAWMA. 47: 524-529.
- Watson, J. G., Chow, J.C., Lu, Z., Fujita, E.M., Lowenthal, D.H. and Lawson, D.R. (1994).
 Chemical Mass Balance Source Apportionment of PM₁₀ During the Southern California Air Quality Study. *Aerosol Sci. Technol.* 21: 1-36.
- Watson, J.G., Chow, J.C. and Pace, T.G. (1991). Chemical Mass Balance Receptor Modeling for Air Quality Management, Hopke, P.K. editor. Elsevier Press, New York, NY, 1991, p. 83-116.

- Watson, J.G., Robinson, N.F., Lewis, C.W., Coulter, C.T., Chow, J.C., Fijita, E.M., Lowenthal, D.H., Conner, T.L., Henry, R.C. and Willis, R.D. (1997). *Chemical Mass Balance Receptor Model Version 8 (CMB)*. User Manual, Prepared for US EPA Research Triangle Park, NC, Desert Research Institute, Reno, N.V.USEPA, (2001). CMB8 User Manual, EAP-454/R-01-XXX.
- Yadav, S. and Rajamani, V. (2006). Air Quality and Trace Metal Chemistry of Different

Size Fractions of Aerosols in N–NW India—implications for Source Diversity. *Atmos. Environ.* 40: 698–712.

Zheng, M., Salmon, L.G. Schauer, J.J., Zeng,
L., Kiang, C.S., Zhang, Y. and Cass, G.R.
(2005). Seasonal Trends in PM_{2.5} Source
Contributions in Beijing, China. *Atmos. Environ.* 39: 3967–4166.

> Received for review, September 16, 2007 Accepted, February 28, 2008